

JIS FLANGE 16KG/CM²




JIS FLANGE
BLIND



JIS FLANGE
PLATE



JIS FLANGE
SLIP-ON



UNIT:MM

PIPE		PIPE	Bo (2)		D (2)		t (2)		T (2)		G (2)		f	r	H (2)		X (2)		C (2)		Number of Holes	Bolt Diameter	kg/ pc		
B	A																						PL	SO	BL
3/8	10	17.3	17.8		90		12		16		48		1	4	26		28		65		4	15	0.5	0.5	0.6
1/2	15	21.7	22.2		95		12		16		52		1	4	30		32		70		4	15	0.6	0.6	0.6
3/4	20	27.2	27.7		100		14		20		58		1	4	38		42		75		4	15	0.7	0.8	0.8
1	25	34.0	34.5		125		14		20		70		1	4	46		50		90		4	19	1.2	1.2	1.3
1 1/4	32	42.7	43.2	+0.5	135		16	+1.0	22		80		2	5	56		60		100		4	19	1.5	1.6	1.7
1 1/2	40	48.6	49.1	-0	140	+1.0	16	-0	24		85		2	5	62		66	+1.0	105	±0.5	4	19	1.6	1.7	1.8
2	50	60.5	61.1		155	-0	16		24		100		2	5	76	+1.0	80	-0	120		8	19	1.7	1.8	2.1
2 1/2	65	76.3	77.1		175		18		26		120		2	5	94	-0	98		140		8	19	2.4	2.6	3.1
3	80	89.1	90.0		200		20		28	±1.0	135		2	6	108		112		160		8	23	3.5	3.7	4.5
3 1/2	90	101.6	102.6		210		20		30		145		2	6	120		124		170		8	23	3.7	4.0	5.0
4	100	114.3	115.4		225		22		34		160		2	6	134		138		185		8	23	4.5	4.9	6.3
5	125	139.8	141.2		270		22		34		195		2	6	164		170		225		8	25	6.5	7.0	9.2
6	150	165.2	166.6		305		24		38		230		2	6	196		202		260		12	25	8.7	9.6	12.8
7	175	190.7	192.1	+1.0	325		26		40		250		2	6	216		222		280		12	25	10.7	10.9	16.5
8	200	216.3	218.0	-0	350	+1.5	26		40		275		2	6	244		252		305		12	25	10.9	12.1	18.6
9	225	241.8	243.7		385	-0	26		40		325		2	6	266		272	+1.5	335	±0.6	12	27	13.9	14.1	23.1
10	250	267.4	269.5		430		28		44		345		2	6	304	+1.5	312	-0	380		12	27	18.0	20.0	30.6
12	300	318.5	321.0		480		30	1.5	48		395		3	8	354	-0	364		430		16	27	21.5	24.4	40.7
14	350	355.6	358.1		540		34	-0	52	±1.5	440		3	8	398		408		480		16	33	30.8	35.0	57.8
16	400	406.4	409.0		605		38		60		495		3	10	446		456		540		16	33	42.8	46.2	82.2
18	450	457.2	460.0	+1.5	675		40		64		560		3	10	504		514	+2.0	605		20	33	55.1	61.9	107.6
20	500	508.0	511.0	-0	730		42		68		615		3	10	558	+2.0	568	-0	660		20	33	65.1	73.3	133.1
22	550	558.8	562.0		795	+2.0	44		70		670		3	10	612	-0	622		720		20	39	77.9	88.1	164.1
24	600	609.6	613.0		845	-0	46		74		720		3	10	666		676		770	±0.8	24	39	86.0	98.8	193.2
26	650	660.4	664.0	+2.0	895		48		77		770		5	10	704	+2.5	726	+2.5	820		24	39	96.3	101.0	227.5
28	700	711.2	715.0	-0	960		50		80		820		5	10	754	-0	776	-0	875		24	42	114.1	120.0	272.6
30	750	762.0	766.0		1020	+2.5	52	+2.0	83		880		5	10	806		832		935		24	42	132.7	141.0	321.9
32	800	812.8	817.0		1085	-0	54	-0	86		930		5	10	865		885		990		24	48	152.1	161.0	375.6
34	850	863.6	868.0	+2.5	1135		56		89		980		5	10	916	+3.0	936	+3.0	1040		24	48	166.5	177.0	428.1
36	900	914.4	919.0	-0	1185		58		93		1030		5	10	968	-0	986	-0	1090	±1.0	28	48	178.1	191.0	481.8
40	1000	1016.0	1021.0		1320		62		99		1140		5	12	1070		1098		1210		28	56	235.3	230.0	636.0
44	1100	1117.6	1123.0		1420		66		105		1240		5	12	1180		1200		1310		32	56	267.9	289.0	784.0
48	1200	1219.2	1225.0		1530		70		112		1350		5	12	1282		1302		1420		32	56	321.1	348.0	972.4
52	1300	1320.8	1326.0	+3.0	1645		74		-	±2.0	1450		5	-	-	+3.5	-	+3.5	1530		32	62	378.6	-	1185.2
54	1350	1371.6	1377.0	-0	1700	+3.0	76		-		1510		5	-	-	-0	-	-0	1590	±1.5	32	62	410.0	-	1303.8
56	1400	1422.4	1428.0		1755		78		-		1560		5	-	-		-		1640		36	62	436.0	-	1422.5
60	1500	1524.0	1529.0		1865		80		-		1670		5	-	-		-		1750		36	62	496.4	-	1656.6