

JIS FLANGE 20KG/CM²




JIS FLANGE
BLIND



JIS FLANGE
PLATE



JIS FLANGE
SLIP-ON



(Dimensions in mm)

PIPE		PIPE	Bo (2)		D (2)		t (2)		T (2)		G (2)		f	r	H (2)		X (2)		C (2)		Number of Holes	Bolt Diameter	kg/ pc		
B	A																						PL SO BL		
3/8	10	17.3	17.8	+0.5 -0	90	+1.0 -0	14	+1.0 -0	20	+1.0	48	±0.8	1	4	30	+1.0	32	+1.0	65	±0.5	4	15	0.6	0.6	0.6
1/2	15	21.7	22.2		95		14		20		52		1	4	34	-0	36	-0	70	4	15	0.7	0.7	0.7	
3/4	20	27.2	27.7		100		16		22		58		1	4	40		42		75	4	15	0.8	0.8	0.9	
1	25	34.0	34.5		125		16		24		70		1	4	48		50		90	4	19	1.3	1.3	1.5	
1 1/4	32	42.7	43.2		135		18		26		80		2	5	56		60		100	4	19	1.6	1.6	1.8	
1 1/2	40	48.6	49.1		140		18		26		85		2	5	62		66		105	4	19	1.7	1.7	2.0	
2	50	60.5	61.1		155		18		26		100		2	5	76		80		120	8	19	1.9	1.9	2.4	
2 1/2	65	76.3	77.1		175		20		30		120		2	5	100		104		140	8	19	2.6	2.6	3.4	
3	80	89.1	90.0		200		22		34		135		2	6	113		117		160	8	23	3.8	3.9	4.9	
3 1/2	90	101.6	102.6		210		24		36		145		2	6	126		130		170	8	23	4.4	4.6	6.0	
4	100	114.3	115.4		225		24		36		160		2	6	138		142		185	8	23	4.9	5.1	6.9	
5	125	139.8	141.2		270		26		40		195		2	6	166		172		225	8	25	7.8	8.3	11.0	
6	150	165.2	166.6	+1.0 -0	305	+1.5 -0	28	+1.5 -0	42	230	±0.9	2	6	196		202		260	±0.6	12	25	10.1	10.6	14.9	
7	175	190.7	192.1		325		30		46	250		2	6	218		226		280		12	25	12.0	12.1	19.0	
8	200	216.3	218.0		350		30		46	275		2	6	244		252		305		12	25	12.6	13.3	21.4	
9	225	241.8	243.7		385		32		48	300		2	6	266		274	+1.5	335		12	27	16.0	16.3	28.5	
10	250	267.4	269.5		430		34		52	345		2	6	304	+1.5	312	-0	380		12	27	21.9	23.4	37.2	
12	300	318.5	321.0		480		36		56	395		3	8	354	-0	364		430		16	27	25.8	27.7	48.8	
14	350	355.6	358.1		540		40		62	440		3	8	398		408		480		16	33	36.2	39.2	68.0	
16	400	406.4	409.0		605	+2.0 -0	46		70	±1.5	495	±1.0	3	10	446		456			540	16	33	51.7	54.2	99.4
18	450	457.2	460.0		675		48		78		560		3	10	504	+2.0	514	+2.0	605	±0.8	20	33	66.1	71.7	129.1
20	500	508.0	511.0		730		50		84		615		3	10	558	-0	568	-0	660		20	33	77.4	86.2	158.4
22	550	558.8	562.0		795		52		90		670		3	10	612		622		720		20	39	92.2	105.0	194.0
24	600	609.6	613.0		845		54		96		720		3	10	666		676		770		24	39	101.1	119.0	226.9
26	650	660.4	664.0		945		60		-		790		5	-	-		-		850		24	48	147.6	-	311.6
28	700	711.2	715.0		995		64		-		840		5	-	-		-		900		24	48	168.0	-	370.9
30	750	762.0	766.0		1080	+2.5 -0	68	+2.0 -0	-		900		5	-	-	+2.5	-	+2.5	970	±1.0	24	56	212.7	-	460.1
32	800	812.8	817.0		1140		72		-		960		5	-	-	-0	-	-0	1030		24	56	248.5	-	546.5
34	850	863.6	868.0		1200		74		-		1020	±1.2	5	-	-		-	-	1090		24	56	280.5	-	626.2
36	900	914.4	919.0		1250		76		-		1070		5	-	-		-	-	1140		28	56	296.9	-	694.9